

[Features]

- Built-in magnetic contactor and overload relay for on-site motors and pumps
- Single-phase AC 110V / AC 220V; contactor from 10A to 39A, up to 220V/7HP
- Dry contact and wet contact outputs, for use with DO4, DO8, DO16 or CBA
- Two enclosure sizes (300 / 400); up to 4 loads per panel
- Independent power disconnect for safe maintenance and fault isolation

[Applications] Construction sites, industrial control facilities

[Model Selection]

MCP-Code 1-Code 2-Code 3-Code 4

Code 1	Enclosure	Code 2	Load Voltage	Code 3	Load Current (multi-select)	Code 4	Output Type
300	300*300*180 mm	110	AC 110V	10A	CU-11 110V/0.75HP, 220V/1.5HP	D	Dry Contact (DO4/DO8/DO16)
				14A	CU-16 110V/1HP, 220V/2HP		
				20A	CU-18 110V/1.5HP, 220V/3HP		
400	300*400*180 mm	220	AC 220V	26A	CU-22 110V/2HP, 220V/4HP	W	Wet Contact (CBA)
				35A	CU-32 110V/2HP, 220V/5HP		
				39A	CU-38 110V/3HP, 220V/7HP		

※ Code 1 = 300 → max. 2 Code 3 options; Code 1 = 400 → max. 4 Code 3 options

[Dimensions] Unit: mm

